

CHUFENG MODEL M31A

STARTING FROM
MRP 29,99,999



200,000 KM
5 YEARS BATTERY / MOTOR
WARRENTY*



RANGE 280 km



Battery
41.93KW



Payload
1460 KG



Gradeability
25 DEGREE



ABS + EBD



Peak Power
70 KW



EXTERIOR



Dynamic Front Grille



Durable Utility Wheels



Heavy-Duty Rear Cargo Bed



200 mm Ground Clearance



Spacious Top Cargo Layout



INTERIOR



Driver Cockpit View



Dashboard & Controls



Storages & Utility Space



Front Cabin & Seating



Rear Cabin window view

Dimensions:



Body Color:



SPECIFICATION

Sales Feature Name	Vehicle model
Technical Parameters	M31A
Dimensional Parameters	
Vehicle Length(mm)	4960
Vehicle Width (mm)	1636
Vehicle height (utetheisa kong load) (mm)	2000
Wheelbase (mm)	3000
Compartment Dimensions (mm)	3050*1600*350
Front track (along the ground) (mm)	1420
Rear wheel track (center of dual wheels) (mm)	1390
Front/rear overhang (mm)	580/1380
Quality Parameters	
Curb weight (kg)	1520
Rated load capacity (kg)	1460
Rated total mass (kg)	2980
Permitted front axle load mass (kg)	1200
Permitted rear axle load mass (kg)	1780
Number of occupants (including the driver)	2
Performance Parameters	
Maximum speed (Km/h)	90
Maximum Climbing Gradient (%)	25
Minimum turning diameter (m)	14.5
Minimum ground clearance (mm)	>200
Driving range (Km)	280
Electric motor	
Rated power/Peak power(Kw)	35/ 70
Rated torque / Peak torque (Nm)	90/230
Motor controller	
Rated input voltage (V)/current (A)	336/115
Operating voltage (V) range	220~430
Lithium iron phosphate lithium-ion power battery	
Manufacturer	Tianjin Gotion
Nominal voltage / nominal capacity of battery pack	41.93kwh
Battery cooling system	Air-cooled, with electric heating

Chassis Configuration	
Front axle	ABS axle with self-adjusting brakes.
rear axle	ABS axle with auto slack adjuster
Rear axle assembly main reduction ratio	10.5
Frame Assembly	Trough-shaped joint Broussonetia papyrifera variable cross-section beam
Front suspension	Front spring with 5 leaves, tubular shock absorber
Rear Suspension	Rear spring with 5 leaves, tubular shock absorber
Steering gear assembly	Electric Power Steering
Braking system	Hydraulic brakes, front disc/rear drum, ABS+EBD, mechanical handbrake.
Tire	185R14LT 8PR, 4 pieces, without spare tire
Driver's cab	
Driver's cab	1650mm wide right-hand drive cab-over type, non-tilting, without wind deflector
Driver's seat	Spring shock-absorbing seat, fabric
Electrical appliance	
Air conditioning system	no Air conditioning, warm air
Fog light	Standard configuration
Central locking system	Without central locking system
Electric window regulator	Without electric lifting device
Rearview mirror	Manual rearview mirror
USB	Cigarette lighter with USB port
Charging method	Slow charging 3.3kw, fast charging
Braking system	Hydraulic brakes, front disc/rear drum, ABS+EBD, mechanical handbrake.
Tire	185R14LT 8PR, 4 pieces, without spare tire

 **Showroom:** Baluwatar, kathmandu
 **Service Center:** Kalopool kathmandu
 +977-01-449331
 +977 980-2367408
 www.lifematters.com.np
 chufengnepal@gmail.com

DEALER STAMP:



Follow us on:



DISCLAIMER: SPECIFICATIONS, PICTURES & COLORS ARE SUBJECT TO CHANGE AND MAY DIFFER FROM THE ACTUAL VEHICLE. FOR LATEST INFORMATION PLEASE CONTACT YOUR LOCAL DEALERS.